

Material Safety Data Sheet

IDENTIFICATION OF THE MATERIAL AND SUPPLIER SECTION 1.

Product Name INOX-mx3

Manufacturers Code

00003 – 100 g Aerosol 00001 – 300 g Aerosol

Recommended Use Anti-corrosion / anti-moisture - penetrating oil.

Company Name

CANDAN INDUSTRIES PTY LTD

Address

65 Chetwynd Street LOGANHOLME Q 4129

AUSTRALIA

Emergency Tel 0439 788 748 (5 p.m. - 8 a.m.) weekdays. 24 Hours weekends and Public

Holidays.

Phone 07 3209 8733 07 3209 8744 Fax

> **SECTION 2.** HAZARDS IDENTIFICATION

Hazard Classification Not classified as hazardous according to the criteria of Safe Work Australia.

Classified as a Dangerous Good according to the Australian Dangerous

Goods (ADG) Code.

Risk Phrases R12 Extremely flammable

Safety Phrases S2 Keep out of reach of children

S9 Keep container in a well ventilated place S16 Keep away from sources of ignition.

COMPOSITION/INFORMATION ON INGREDIENTS SECTION 3.

Ingredients Name CAS Proportion %

106-97-8 · < 30% Butane 74-98-6 < 10% Propane Ingredients determined not to be To 100%

hazardous



SECTION 4. FIRST AID MEASURES

Swallowed Do not induce vomiting, give 1 to 2 glasses of water to drink. Seek medical

Irrigate thoroughly with water, if irritation occurs, seek medical advice. Eye Skin

Wash area with soap and water. Remove contaminated clothes and launder

before reuse.

Inhaled Remove from further exposure. If irritation, dizziness, nausea or

> unconsciousness occurs, get medical assistance. If breathing is shallow or has stopped, ensure airways are clear and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained.

First Aid Facilities Aggravated medical conditions caused by exposure.

No special facilities required

None known.

Chronic Health Effects

Prolonged or repeated contact with this material may result in skin irritation

leading to dermatitis.

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher Hazards from combustion products Special protective precautions and equipment for fire fighters

Foam, Carbon dioxide and dry chemical powder.

Carbon monoxide (CO)

Self-Contained Breathing Apparatus (SCBA) and full protective clothing should

be worn for fires in enclosed areas..

Hazchem code 2YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency procedures Eliminate all sources of ignition and ventilate area.

Methods and materials for containment and clean up.

Clean up all spills immediately.

Avoid breathing vapours and contact with skin and eyes.

If safe to do so, damaged cans should be placed into a container in a well

ventilated area (outside) until the gas has discharged.

Clean up spills with inert material and dispose of in accordance with current

legislation.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Conditions for safe storage including any incompatibilities

Use in a well ventilated area. Do not store or use in confined spaces.

Classified as a Flammable gas for storage and handling purposes. Store in a cool, dry, well ventilated area, out of direct sunlight. Avoid sparks, flames and other ignition sources.

Store away from incompatible materials such as oxidising materials and flammable liquids

Prepared: January 2015

Printed:04/02/15 Page 2 of 5



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure standards for

No value assigned for this specific material by Safe Work Australia

mixture

Component **Breathing Zone** Mixture conc. (%)

TWA ppm TWA mg/m³ STEL ppm STEL mg/m³

<30% **Butane** 800 1900 **Propane** < 10%

Biological Limit

No biological limit allocated

Values Engineering

Use in well ventilated areas.

Controls

Personal Protective Equipment

Very mild irritant therefore the use of Safety glasses is recommended. Eyes.

Hands/Feet Safety footwear.

Other Non irritant. Good personal hygiene recommended.

Respirator No special requirements under ordinary conditions of use and with adequate

ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear light tan liquid Minimal odour Odour рΗ Not applicable < 6kPa . Vapour pressure LEL < 4% Flammability Limits UEL - not known

Flashpoint 182°C when propellant gas has dissipated.

Pour Point - 18°C Solubility in water Negligible Density 0.840

SECTION 10. STABILITY AND REACTIVITY

Chemical stability Stable under normal conditions

Conditions to avoid Avoid extreme heat.

Incompatible materials Strong oxidizing agents, Flammable liquids and Corrosive materials. Carbon monoxide (CO)

Hazardous decomposition

products

Hazardous reactions No hazardous polymerization will occur



SECTION 11. TOXICOLOGICAL INFORMATION

Halogens: None **Carcinogens:** None

Inhaled: Inhalation of mists and aerosols may produce respiratory irritation and coughing. Inhalation

of high concentrations may lead to respiratory collapse.

Skin contact: Non irritant

Eyes contact: Mild irritant

Swallowed: May cause stomach upset.

SECTION 12. ECOLOGICAL INFORMATION

No data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods and

Dispose of waste according to federal, EPA and state regulations

containers

Special precautions for Do Not incinerate or puncture aerosol cans.

landfill or incineration

Bury residues and emptied cans at an approved site.

SECTION 14. TRANSPORT INFORMATION

UN Number 1950 UN Proper shipping Aerosols

name
Class 2.1
Subsidiary risk None

Packing Group None allocated

Special precautions for Use in well ventilated work areas.

user

Hazchem Code 2YE

SECTION 15. REGULATORY INFORMATION

Food Grade Approvals

New Zealand: NZ FSA Approved C12 (All animal product except dairy)

N.A.T.O. Defence Manufactures Code No. Z5594/5

KOSHER Certificate - FKD - HCTN Pareve

Poison Schedule Not scheduled

Prepared: January 2015 Printed:04/02/15 Page 4 of 5

SECTION 16. OTHER INFORMATION

Date of Preparation: 30th January 2015

Contact Person

Colin Ford - Senior Production Manager

Loganholme Q. Australia
Telephone: 61 7 3209 8733
Email: info@inoxmx.com
Website: www.inoxmx.com

Literature references.

List of Designated Hazardous Substances.

Hazardous Substance Information System http://hsis.ascc.gov.au/

National Code of Practice for the Preparation of Material Safety Data Sheets 2^{nd} edition [NOHSC:2001(2003)].

Abbreviations:

NOHSC National Occupational Health and Safety Commission

TWA Time weighted average

STEL Short term exposure limit

CAS Number Chemical Abstract Service registry number

TLV Threshold limit value

Safety data sheets are updated frequently. Please ensure that you have a current copy.

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use hereof. Candan Industries Pty Ltd assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material, Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The user must determine whether the use of the information and data is in accordance with local laws and regulations.

END OF MSDS

Prepared: January 2015 Printed:04/02/15 Page 5 of 5