

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: EX2002
Product Name: Export Water-Based Acting Fly Spray, 250gms
Revision Date: Sep 01, 2025 **Date Printed:** Sep 01, 2025
Version: 2.0 **Supersedes Date:** Aug 12, 2020
Manufacturer's Name: Paragon Aerosol & Volumetric Filling
Address: 3-5 Hannabus Place
Mulgrave NSW 2756
Emergency Phone: 13 11 26
Information Phone Number: 02 4577 6977
Product/Recommended Uses: Insect killer

SECTION 2) HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.

Classification

Aerosols Category 1
 Aspiration Hazard - Category 1
 Chronic aquatic toxicity - Category 2
 Skin Irritation - Category 2
 Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Pictograms



Signal Word

Danger

Poisons Schedule

Not applicable

Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H336 - May cause drowsiness or dizziness

Hazardous Statements - Physical

H222 - Extremely flammable aerosol

Hazardous Statements - Environmental

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P264 - Wash hands, face and exposed skin thoroughly after handling.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 - Use only outdoors or in a well-ventilated area.

P233 - Keep container tightly closed.

Precautionary Statements - Response

P312 - Call a POISON CENTER/doctor/physician if you feel unwell.

P321 - Specific treatment- see First Aid on this label.

P378 - Use dry chemical, foam, carbon dioxide to extinguish.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P405 - Store locked up.

P403 - Store in a well-ventilated place.

Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local, regional, national and international regulations.

SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS

| CAS | Chemical Name | % By Weight |
|--------------|------------------------------------|-------------|
| 0000106-97-8 | BUTANE | 30% - 60% |
| 0064742-47-8 | ISOPARAFFINIC PETROLEUM DISTILLATE | 10% - 30% |
| 0000074-98-6 | PROPANE | 10% - 30% |
| 0000051-03-6 | PIPERONYL BUTOXIDE | <0.5% |
| 0007696-12-0 | TETRAMETHRIN | <0.5 % |
| 0026002-80-2 | PHENOTHRIN | <0.5 % |

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Eliminate all ignition sources if safe to do so. Remove source of exposure or move person to fresh air, keep comfortable for breathing and keep warm. If you feel unwell/if concerned: Get medical advice/attention.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention. Take care not to rinse contaminated water into the unaffected eye or onto the face.

Skin Contact

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Avoid direct contact. Wear chemical protective clothing, if necessary. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. Wash contaminated clothing before re-use or discard. If skin irritation occurs: Get medical advice/attention.

Ingestion

Rinse mouth. Never give anything by mouth to an unconscious or convulsing person. Give a glass of water to drink. Do NOT induce vomiting. If vomiting occurs naturally, give further water. Immediately call a POISON CENTER/doctor. If vomiting occurs give further water. Get to a doctor or hospital quickly.

Most Important Symptoms and Effects, Both acute and Delayed

No data available.

Indication of Any Immediate Medical Attention and Special Treatment Needed

Treat symptomatically.

PPE for First Aiders: Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use caution when applying carbon dioxide in confined spaces. Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Large Fire: Water spray, fog or alcohol-resistant foam. For Chlorosilanes: Do not use water; use AFFF alcohol-resistant medium-expansion foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards in Case of Fire

Flammable gas. Ruptured cylinders may rocket. Vapors may travel to source of ignition and flash back. May form an ignitable vapor/air mixture in closed tanks or containers. Runoff may create fire or explosion hazard. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. May form flammable vapour mixtures with air. Cylinders exposed to fire may vent and release toxic gas through pressure relief devices. On burning or decomposing may emit toxic fumes. Electrical requirements for work area should be assessed according to AS3000. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters. Damaged cylinders should be handled only by specialists. Large Fire: Dike fire-control water for later disposal; do not scatter the material. Heating can cause expansion or decomposition leading to violent rupture of containers. Use shielding to protect against bursting containers. Stop the flow of gas and use water spray to disperse vapors. Large Fire: Damaged cylinders should be handled only by specialists.

Special Protective Actions

Wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate and isolate hazard area and keep unauthorized personnel away. Do not walk through released material. Stay upwind of release. Ventilate closed spaces before entering. A vapor-suppressing foam may be used to reduce vapors.

Recommended Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

DO NOT breathe gas, vapor or mist.

DO NOT get on skin, eyes or clothing.

Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Suppress aerosol with water spray jet. Neutralization may be required before discharging sewage into treatment plants. Dike far ahead of liquid spill for later disposal.

Methods and Materials for Containment and Cleaning up

Rinse away with water. Clean up immediately. Ventilate area after clean-up is complete. Use clean, non-sparking tools to collect absorbed material.

For small spills: wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

For large spills: absorb with vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

SECTION 7) HANDLING AND STORAGE

General

Remove contaminated clothing and protective equipment before entering eating areas. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors, mists or aerosols. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. This product is not intended for human or animal consumption. Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Provide secondary containment for toxic materials. Store gas cylinders separately, away from processing and handling areas, and from incompatible materials. Eliminate all sources of ignition. Protect containers against banging or other physical damage when storing, transferring, or using them. Keep containers securely sealed when not in use, check regularly for leaks. Store at temperatures above their respective freezing/melting point, do not expose to temperatures exceeding 50 °C/122 °F. Empty containers retain residue and may be dangerous. Store in dry, well-ventilated, cool areas, out of direct sunlight and away from incompatible materials and other sources of heat. Never use plastic or glass containers for storing flammable liquids. Check regularly for leaks. This material is classified as a Dangerous Good Class 2.1 Flammable Gas as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear safety glasses with side shields.

Skin Protection

Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Wear a Face Shield. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment.

Respiratory protection

If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Natural ventilation should be adequate under normal use conditions.

| Chemical Name | ACGIH TWA (mg/m ³) | ACGIH STEL (ppm) | ACGIH STEL (mg/m ³) | ACGIH TWA (ppm) | ACGIH Carcinogen | ACGIH TLV Basis | ACGIH Notations | WES TWA (mg/m ³) |
|------------------------------------|---|--|---------------------------------|--------------------|---|----------------------------|---|------------------------------|
| BUTANE | | 1000 (EX) | | | | CNS impair | | 1900 |
| ISOPARAFFINIC PETROLEUM DISTILLATE | [(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]]; | | | (L)[N159](L)[N800] | [A2[N159]A2[N800]]; [A4[N159]A4[N800]]; | URT irr[N159]URT irr[N800] | [A2[N159]A2[N800]]; [A4[N159]A4[N800]]; | |
| PROPANE | | Simple asphyxiant (D), explosion hazard (EX) | | | | Asphyxia | | |

| Chemical Name | WES STEL (ppm) | WES STEL (mg/m ³) | WES TWA (ppm) | WES HEALTH | OSHA TWA (ppm) | OSHA TWA (mg/m ³) | OSHA STEL (ppm) | OSHA STEL (mg/m ³) |
|------------------------------------|----------------|-------------------------------|---------------|------------|----------------|-------------------------------|-----------------|--------------------------------|
| BUTANE | | | 800 | | | | | |
| ISOPARAFFINIC PETROLEUM DISTILLATE | | | | | 500 | 2000 | | |
| PROPANE | | | | | 1000 | 1800 | | |

| Chemical Name | OSHA Skin designation | OSHA Carcinogen |
|------------------------------------|-----------------------|-----------------|
| BUTANE | | |
| ISOPARAFFINIC PETROLEUM DISTILLATE | | |
| PROPANE | | |

(C) - Ceiling limit, CNS - Central nervous system, impair - Impairment, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

| | |
|-------------------------|--------------------|
| Density | 7.76 lb/gal |
| Specific Gravity | 0.93 |
| % VOC | 98.92% |
| Density VOC | 7.68 lb/gal |
| % Solids By Weight | 0.00% |
| Appearance | Clear liquid |
| Odor Description | No odour |
| Odor Threshold | Data not available |
| pH | Data not available |
| Water Solubility | Data not available |
| VOC Part A & B Combined | Data not available |
| Flash Point Symbol | < |
| Flash Point | 0 °C |
| Viscosity | Data not available |
| Lower Explosion Level | Data not available |
| Vapor Pressure | Data not available |
| Upper Explosion Level | Data not available |
| Vapor Density | Data not available |
| Freezing Point | Data not available |
| Melting Point | Data not available |
| Low Boiling Point | Data not available |
| High Boiling Point | Data not available |
| Auto Ignition Temp | Data not available |
| Decomposition Pt | Data not available |
| Evaporation Rate | Data not available |
| Coefficient Water/Oil | Data not available |

SECTION 10) STABILITY AND REACTIVITY

Stability

The product is stable under normal storage conditions.

Conditions to Avoid

Avoid heat, sparks, flame, elevated temperatures, sources of ignition and contact with incompatible materials. Elevated temperatures and sources of ignition.

Hazardous Reactions/Polymerization

Will not occur.

Incompatible materials

Oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon and nitrogen, smoke and other toxic fumes.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

Causes skin irritation

Carcinogenicity

No data available.

Serious Eye Damage/Irritation

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

The vapour is mildly irritating to the eyes.

Respiratory/Skin Sensitization

Material may be an irritant to mucous membranes and respiratory tract.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

The substance defats the skin, which may cause dryness or cracking.

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination and impaired judgment.

May cause drowsiness or dizziness

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

May cause effects on the central nervous system.

Specific Target Organ Toxicity - Repeated Exposure

Prolonged exposure to inhalation of high concentration can lead to unconsciousness.

Aspiration Hazard

Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

May be fatal if swallowed and enters airways

Acute Toxicity

Inhalation of vapour can result in headaches, dizziness and possible nausea.

Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

If swallowed, can easily enter the airways and could result in aspiration pneumonitis.

If swallowed, can easily enter the airways and could result in aspiration pneumonitis. Inhalation of high concentrations may cause dizziness, anesthesia, unconsciousness.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

0000106-97-8 BUTANE

The substance can be absorbed into the body by inhalation.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

0000106-97-8 BUTANE

LC50 (mouse): 202000 ppm (481000 mg/m³) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9)

LC50 (rat): 276000 ppm (658000 mg/m³) (4-hour exposure); cited as 658 mg/L (4-hour exposure) (9)

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Toxic to aquatic life with long lasting effects

Persistence and Degradability

0000106-97-8 BUTANE

Readily biodegradable.

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Expected to be inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.

Bio-accumulative Potential

No data available.

Mobility in Soil

0064742-47-8 ISOPARAFFINIC PETROLEUM DISTILLATE

Floats on water. Contains volatile constituents. Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000106-97-8 BUTANE

Readily biodegradable.

This substance is not PBT/vPvB

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

ADG Information

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN number: 1950

Proper shipping name: AEROSOLS

Hazard class: 2.1

Packaging group: None

IMDG Information

This material is classified as a marine Pollutant (P) according to the International Maritime Dangerous Goods Code.

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea

UN number: 1950

Proper shipping name: AEROSOLS

Hazard class: 2.1

Packaging group: None

IATA Information

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN number: 1950

Proper shipping name: AEROSOLS

Hazard class: 2.1

Packaging group: None

SECTION 15) REGULATORY INFORMATION**This material is not subject to the following international agreements:**

Montreal Protocol (Ozone depleting substances)
 The Stockholm Convention (Persistent Organic Pollutants)
 The Rotterdam Convention (Prior Informed Consent)
 Basel Convention (Hazardous Waste)
 International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): Not Applicable.

AICIS Status: All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).

SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS**Glossary**

ACGIH- American Conference of Governmental Industrial Hygienists; ADG- Australian Dangerous Goods Code; CAS- Chemical Abstract Service; DSL- Domestic Substances List; LC- Lethal Concentration; LD- Lethal Dose; OSHA- Occupational Safety and Health Administration; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; VOC- Volatile Organic Compounds; WES- Workplace Exposure Standards

Version 2.0:

Revision Date: Sep 01, 2025

Second Edition.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.