



Safety Data Sheet

Hazardous, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: ISOWASH 30F

Recommended use: Cleaner/ Solvent

Supplier: Aim Chemicals Pty Ltd

ABN: 15 069 029 232

Street Address: 171 Thornside Road

Thorneside

Queensland

4158

Telephone: (07) 3207 1033

Facsimile: (07) 3207 1044

Email: info@aimgroup.com.au

Emergency Telephone number: (07) 3207 1033 (24hr)

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.



Signal Word

Danger

Hazard Classifications

Flammable Liquids - Category 3

Aspiration Hazard - Category 1

Skin Corrosion/Irritation - Category 3

Specific Target Organ Toxicity (Single Exposure) - Category 3 Respiratory Tract Irritation

Acute Hazard to the Aquatic Environment - Category 3

Chronic Hazard to the Aquatic Environment - Category 3

Hazard Statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust, fume, gas, mist, vapours or spray..
P271 Use only outdoors or in a well-ventilated area.



Safety Data Sheet

P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing including eye/face protection and suitable respirator.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P331 Do NOT induce vomiting.
P370+P378 In case of fire: Use (insert appropriate media) to extinguish.

Storage Precautionary Statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule:

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Naphtha, petroleum, hydrotreated heavy	64742-48-9	100 %
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.

Eye contact: No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.



Safety Data Sheet

Ingestion: Seek immediate medical attention. Do not induce vomiting.

PPE for First Aiders: Wear safety shoes, overalls, gloves, apron, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

5. FIRE FIGHTING MEASURES

Hazchem Code: 3Y

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.



Safety Data Sheet

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, APRON, CHEMICAL GOGGLES, RESPIRATOR.



Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, overalls, gloves, apron, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Clear Liquid

Colour: Clear colourless liquid

Odour: Mild Petroleum/Solvent

Solubility in water: Negligible

Specific Gravity: 0.764

Relative Vapour Density (air=1): >1 Air = 1

Vapour Pressure (20 °C): 0.46 kPa (@ 20 °C)

Flash Point (°C): 30 °C

Autoignition Temperature (°C): >200 °C

Melting Point/Range (°C): No Data Available

Boiling Point/Range (°C): 130 - 166 °C @ 100kPa

pH: No Data Available

Viscosity: 0.86 cSt (0.86 mm²/sec) at 40°C - 1.02 cSt (1.02 mm²/sec) at 25°C (41) No Data Available)

Evaporation Rate (n-Butyl acetate=1): 0.35 (n-butyl acetate = 1)

(Typical values only - consult specification sheet)



Safety Data Sheet

N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This product is unlikely to react or decompose under normal storage conditions.

Conditions to avoid: This product should be kept in a cool place, preferably below 30 deg C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatible materials: Strong acids, strong oxidising agents.

Hazardous decomposition products: Material does not decompose at ambient temperatures.

Hazardous reactions: Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Short Term Exposure: Available data indicates that this product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucus in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased. Long Term Exposure: No data for health effects associated with long term inhalation. Inhalation of aliphatic hydrocarbon vapours seems to show little toxicity but are CNS depressants and have a disinhibiting euphoric effect.

Skin contact: Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort. Long Term Exposure: Repeated exposure may cause skin dryness or cracking. Prolonged dermal exposure to white spirit, e.g., resulting from wearing clothes that have been soaked or moistened by white spirit for hours, may produce irritation and dermatitis. Single cases of acute toxicity to the kidney, liver and bone marrow have been reported following exposure to white spirit at high levels. However, owing to lack of details and the sporadic nature of the reportings, the relevance of these findings is unclear.

Ingestion: Short Term Exposure: Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased. Long Term Exposure: No data for health effects associated with long term ingestion. Ingestion of white spirit has been reported to produce gastrointestinal irritation with pain, vomiting and diarrhoea. Lesions of the mucous membranes in the oesophagus and the gastrointestinal tract followed the oral exposure. Owing to its low viscosity and low surface tension, white spirit poses a risk of aspiration into the lungs following oral exposure. A few ml of solvent aspirated into the lungs are able to produce serious bronchopneumonia and 10-30ml may be fatal. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

Eye contact: Short Term Exposure: This product may be irritating to eyes, but is unlikely to cause anything more than mild transient discomfort. Long Term Exposure: No data for health effects associated with long term eye exposure.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity

Product Name: ISOWASH 30F

Reference No:

Issued: 2021-12-01

Version:

Page 5 of 8



Safety Data Sheet

estimate (based on ingredients): LC₅₀ > 20.0 mg/L for vapours or LC₅₀ > 5.0 mg/L for dust and mist.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): LD₅₀ > 2,000 mg/Kg bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): LD₅₀ > 2,000 mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitisier. Skin: this material has been classified as not a skin sensitisier.

Aspiration hazard: This material has been classified as Aspiration Hazard - Category 1

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

Specific target organ toxicity (repeat exposure): This material has been classified as not a specific hazard to target organs by repeat exposure.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as a Category Acute 3 Hazard. Acute toxicity estimate (based on ingredients): > 10 ≤ 100 mg/L

Long-term aquatic hazard: No Data Available

Ecotoxicity: Expected to be harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment. OTHER ECOLOGICAL INFORMATION - VOC: Yes

Persistence and degradability: Biodegradation : Material -- Expected to be readily biodegradable. Hydrolysis : Material -- Transformation due to hydrolysis not expected to be significant. Photolysis : Material -- Transformation due to photolysis not expected to be significant. Atmospheric Oxidation : Material -- Expected to degrade rapidly in air

Bioaccumulative potential: The low water solubility and moderate vapour pressure of products or this type suggest that volatilization and subsequent photo-oxidation are important processes for abiotic degradation in the atmosphere. The octanol/water partition coefficient (log Pow) of hydrocarbon (17% v/v aromatics) has been found to be 3.5 to 6.4. This indicates a moderate potential for bioaccumulation by organisms from water and a likelihood of partitioning to fat within organisms. Note however that this information may not be completely applicable to this low aromatic product.

Mobility: Highly volatile, will partition rapidly to air. Not expected to partition to sediment and waste water solids.

13. DISPOSAL CONSIDERATIONS

Product Name: ISOWASH 30F

Reference No:

Issued: 2021-12-01

Version:

Page 6 of 8



Safety Data Sheet

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 3295
Dangerous Goods Class: 3
Packing Group: III
Hazchem Code: 3Y
Emergency Response Guide No: 14
Limited Quantities 5 L

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S.

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 3295
Dangerous Goods Class: 3
Packing Group: III

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S.

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Safety Data Sheet



UN No: 3295

Dangerous Goods Class: 3

Packing Group: III

Proper Shipping Name: HYDROCARBONS, LIQUID, N.O.S.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): .

16. OTHER INFORMATION

Reason for issue: 5 Yearly Revision

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.