

<b>Product Type:</b>	PVC Cable Wrap Tape																		
<b>Colour:</b>	Translucent																		
<b>Roll Size:</b>	19mm in 20m Rolls retail wrapped (packed 10 to pillow & 160 per Carton)																		
<b>Adhesive:</b>	Rubber Natural																		
<b>Description:</b>	A Lead-Free PVC Electrical Insulation/Cable Wrap tape. Offers good conformability. Excellent UV resistance affording good protection against abrasion, alkalis, acids and corrosion. GT6 is both RoHS & REACH Third Party Tested and Compliant.																		
<b>Application:</b>	Bundling and holding of cables (particularly to staging and scaffolds), loom harnessing, stopping off in plating, prevention of electrolytic corrosion, packaging applications, drum or tube sealing.																		
<b>Technical Details:</b>	<table><tbody><tr><td>Gauge:</td><td>0.12mm</td></tr><tr><td>Tensile Strength (ASTM D-1000):</td><td>24 N/cm</td></tr><tr><td>Elongation at Break (ASTM D-3759):</td><td>220%</td></tr><tr><td>Adhesion to Steel (ASTM D-1000):</td><td>1.5 N/cm</td></tr><tr><td>Adhesion to Self (ASTM D-330):</td><td>1.5 N/cm</td></tr><tr><td>Electrical Breakdown (ASTM D-1000):</td><td>6.0 kV</td></tr><tr><td>Service Temperature:</td><td>-5°C to 80°C</td></tr><tr><td>Application Temperature:</td><td>0°C to 40°C</td></tr><tr><td>Storage Temperature:</td><td>12°C to 25°C</td></tr></tbody></table>	Gauge:	0.12mm	Tensile Strength (ASTM D-1000):	24 N/cm	Elongation at Break (ASTM D-3759):	220%	Adhesion to Steel (ASTM D-1000):	1.5 N/cm	Adhesion to Self (ASTM D-330):	1.5 N/cm	Electrical Breakdown (ASTM D-1000):	6.0 kV	Service Temperature:	-5°C to 80°C	Application Temperature:	0°C to 40°C	Storage Temperature:	12°C to 25°C
Gauge:	0.12mm																		
Tensile Strength (ASTM D-1000):	24 N/cm																		
Elongation at Break (ASTM D-3759):	220%																		
Adhesion to Steel (ASTM D-1000):	1.5 N/cm																		
Adhesion to Self (ASTM D-330):	1.5 N/cm																		
Electrical Breakdown (ASTM D-1000):	6.0 kV																		
Service Temperature:	-5°C to 80°C																		
Application Temperature:	0°C to 40°C																		
Storage Temperature:	12°C to 25°C																		
<b>Surface Preparation:</b>	The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 30°C.																		
<b>Storage:</b>	Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.																		

**DISCLAIMER:**

**Values:** All values presented have been determined by standard test methods and are average values only.

**Recommendations:** Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

**Warranty:** We can only warranty our products to the level that they are consistent with our Product Information Sheet values

**BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.**