

**Product Type:** Polyethylene Laminated Cloth Tape

**Colour:** Yellow/Black Diagonal Stripe

**Roll Size:** 6mm to 1300mm in 25m Lengths

**Adhesive:** Rubber Natural



**Description:** A high quality polyethylene laminated cloth with a rubber adhesive offering high flexibility and conformability.

**Application:** Used to signify the presence of hazards in the industrial and commercial situations. It has an easy-tear cloth and is suitable for use on floors and vertical surfaces. It can be used to delineate safe walkways to separate pedestrians from forklifts and highlight potential hazards such as low headroom and obstructions like posts and bollards.

**Technical Details:**

Gauge:	0.26mm
Tensile Strength:	78 N/cm
Elongation at Break:	10%
Adhesion to Steel:	2.9 N/cm
Service Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Shelf Life:	12 Months

**Surface Preparation:** The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

**Storage:** Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

**Product Demo:** <https://youtu.be/J1-uL415TDE>

**DISCLAIMER:**

**Values:** All values presented have been determined by standard test methods and are average values only.

**Recommendations:** Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

**Warranty:** We can only warranty our products to the level that they are consistent with our Product Information Sheet values

**BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.**

